



**PIPE WEIGHT CHART**

NOMINAL PIPE SIZE	OUTSIDE DIAMETER	WALL THICKNESS	INSIDE DIAMETER	WEIGHT PER FOOT	SCHEDULE	JTS PER LOAD (Based on 40ft jts)	LOAD WEIGHT	SCH NO
3/8"	0.675	0.091	0.493	0.568	STD			40
3/8"	0.675	0.126	0.423	0.739	XHY			80
1/2"	0.840	0.109	0.622	0.852	STD			40
1/2"	0.840	0.147	0.546	1.089	XHY			80
3/4"	1.050	0.113	0.824	1.132	STD			40
3/4"	1.050	0.154	0.742	1.475	XHY			80
1"	1.315	0.133	1.049	1.681	STD			40
1"	1.315	0.179	0.957	2.174	XHY			80
1-1/4"	1.660	0.109	1.442	1.807				10
1-1/4"	1.660	0.140	1.380	2.275	STD			40
1-1/4"	1.660	0.191	1.278	2.999	XHY			80
1-1/2"	1.900	0.145	1.610	2.720	STD			40
1-1/2"	1.900	0.200	1.500	3.635	XHY			80
1-1/2"	1.900	0.281	1.338	4.863				160
2"	2.375	0.109	2.157	2.640				10
2"	2.375	0.154	2.067	3.656	STD			40
2"	2.375	0.218	1.939	5.027	XHY			80
2"	2.375	0.344	1.687	7.469				160
2-1/2"	2.875	0.203	2.469	5.798	STD			40
2-1/2"	2.875	0.276	2.323	7.668	XHY			80
3"	3.500	0.120	3.260	4.336				10
3"	3.500	0.216	3.068	7.583	STD			40
3"	3.500	0.300	2.900	10.262	XHY			80
3"	3.500	0.438	2.624	14.337				160
4"	4.500	0.237	4.026	10.800	STD			40
4"	4.500	0.337	3.826	14.997	XHY			80
5"	5.563	0.258	5.047	14.631	STD			40
5"	5.563	0.375	4.813	20.797	XHY			80
5"	5.563	0.500	4.563	27.062				120
6"	6.625	0.134	6.357	9.298				10
6"	6.625	0.156	6.313	10.788				
6"	6.625	0.188	6.249	12.937				
6"	6.625	0.280	6.065	18.992	STD			40
6"	6.625	0.432	5.761	28.600	XHY			80
8"	8.625	0.188	8.249	16.956				
8"	8.625	0.250	8.125	22.382				20
8"	8.625	0.322	7.981	28.580	STD			40
8"	8.625	0.406	7.813	35.672				60
8"	8.625	0.500	7.625	43.428	XHY			80
10"	10.750	0.188	10.374	21.227				
10"	10.750	0.250	10.250	28.061				20
10"	10.750	0.365	10.020	40.521	STD			40
10"	10.750	0.500	9.750	54.786	XHY			60
10"	10.750	0.594	9.562	64.489				80
12"	12.750	0.219	12.312	29.336				
12"	12.750	0.250	12.250	33.406				20
12"	12.750	0.375	12.000	49.608	STD			
12"	12.750	0.406	11.938	53.575				40
12"	12.750	0.500	11.750	65.476	XHY			
12"	12.750	0.688	11.374	88.713				80
14"	14.000	0.250	13.500	36.747				10
14"	14.000	0.375	13.250	54.619	STD			30
14"	14.000	0.438	13.124	63.500				40
14"	14.000	0.500	13.000	72.158	XHY			
14"	14.000	0.750	12.500	106.232				80



**PIPE WEIGHT CHART**

NOMINAL PIPE SIZE	OUTSIDE DIAMETER	WALL THICKNESS	INSIDE DIAMETER	WEIGHT PER FOOT	SCHEDULE	JTS PER LOAD (Based on 40ft jts)	LOAD WEIGHT	SCH NO
16"	16.000	0.250	15.500	42.092		27	45,459	10
16"	16.000	0.375	15.250	62.637	STD	18	45,098	30
16"	16.000	0.500	15.000	82.848	XHY	13	43,081	40
16"	16.000	0.812	14.376	131.836		8	42,188	80
18"	18.000	0.250	17.500	47.437		24	45,539	
18"	18.000	0.375	17.250	70.654	STD	16	45,219	
18"	18.000	0.500	17.000	93.538	XHY	12	44,898	
18"	18.000	0.562	16.876	104.764		10	41,905	40
18"	18.000	0.938	16.124	171.084		6	41,060	80
20"	20.000	0.250	19.500	52.782		16	33,780	
20"	20.000	0.375	19.250	78.672	STD	14	44,056	20
20"	20.000	0.500	19.000	104.228	XHY	11	45,860	30
20"	20.000	0.594	18.812	123.225		9	44,361	40
20"	20.000	1.031	17.938	209.065		5	41,813	80
22"	22.000	0.375	21.250	86.689	STD	13	45,078	20
22"	22.000	0.500	21.000	114.918	XHY	10	45,967	30
22"	22.000	0.875	20.250	197.598		5	39,520	60
22"	22.000	1.125	19.750	251.048		4	40,168	80
24"	24.000	0.250	23.500	63.472		16	40,622	
24"	24.000	0.375	23.250	94.707	STD	12	45,459	20
24"	24.000	0.500	23.000	125.608	XHY	9	45,219	
24"	24.000	0.688	22.624	171.453		6	41,149	40
24"	24.000	1.219	21.562	296.862		3	35,623	80
26"	26.000	0.250	25.500	68.817		9	24,774	
26"	26.000	0.375	25.250	102.724	STD	9	36,981	
26"	26.000	0.500	25.000	136.298	XHY	8	43,615	20
28"	28.000	0.375	27.250	110.742	STD	9	39,867	
28"	28.000	0.500	27.000	146.988	XHY	7	41,157	20
30"	30.000	0.312	29.376	99.018		9	35,646	10
30"	30.000	0.375	29.250	118.759	STD	9	42,753	
30"	30.000	0.500	29.000	157.678	XHY	7	44,150	20
30"	30.000	0.625	28.750	196.262		5	39,252	30
32"	32.000	0.312	31.376	105.688		9	38,048	10
32"	32.000	0.375	31.250	126.777	STD	9	45,640	
32"	32.000	0.500	31.000	168.368	XHY	6	40,408	20
32"	32.000	0.688	30.624	230.291		5	46,058	40
34"	34.000	0.344	33.312	123.765		4	19,802	10
34"	34.000	0.375	33.250	134.794	STD	4	21,567	
34"	34.000	0.500	33.000	179.058	XHY	4	28,649	20
34"	34.000	0.688	32.624	245.000		4	39,200	40
36"	36.000	0.312	35.376	119.029		4	19,045	10
36"	36.000	0.375	35.250	142.812	STD	4	22,850	
36"	36.000	0.500	35.000	189.748	XHY	4	30,360	20
36"	36.000	0.750	34.500	282.617		4	45,219	40
38"	38.000	0.375	37.250	150.829	STD	4	24,133	
38"	38.000	0.500	37.000	200.438	XHY	4	32,070	
40"	40.000	0.375	39.250	158.847	STD	4	25,415	
40"	40.000	0.500	39.000	211.128	XHY	4	33,780	
42"	42.000	0.375	41.250	166.864	STD	4	26,698	
42"	42.000	0.500	41.000	221.818	XHY	4	35,491	
48"	48.000	0.375	47.250	190.917	STD	4	30,547	
48"	48.000	0.500	47.000	253.888	XHY	4	40,622	
54"	54.000	0.375	53.250	214.969	STD	2	17,198	
54"	54.000	0.500	53.000	285.958	XHY	2	22,877	
60"	60.000	0.375	59.250	239.022	STD	2	19,122	
60"	60.000	0.500	59.000	318.028	XHY	2	25,442	